

IC-R1500	Wideband Receiver with Remote Head Controller for Vehicle (0.010-3299.999MHz) Modes: AM, FM, WFM USB, LSB, CW
IC-R2500	Wideband Receiver with Remote Head Controller for Vehicle (0.010-3299.999MHz) Modes: AM, FM, WFM, USB, LSB, CW, P25 * (*UT122 is required) Both model supplied with the following accessories: DC Power cable, Controller head & cable, USB cable, Antenna and Software CD Additional Requirements when connected to a PC: Microsoft Windows 2000/XP/ME/98SE USB 1.1 or 2.0 Intel Pentium III 450MHz or faster Hard disk with at least 50 MB of free disk space At least 128 MB of memory (256MB or more recommended) Display with 1024x768 pixel resolution, high colour CD-ROM or DVD drive is required for software installation USB audio dropouts or gaps may occur because of a lack of PC processor power Additional hard disk space is required for recording sound or storing scope data

Optional Unit

UT106	DSP unit provides noise reduction
UT108	DTMF Decoder Unit for IC-R2500
UT118	D-Star Digital unit for IC-PCR2500
UT122	P25 Digital Unit for IC-R2500

AC/DC Adaptor

AD113AUS	12V DC, 1.5A power supply
CP12L	12V DC, 2A output from 12V cigarette lighter socket
OPC-254L	DC Power cable - for use with external power supply (12V DC required) as supplied

Cable

OPC-1156	Controller Extension Cable, 3.5m (11.5ft)
----------	---

Speaker

SP10	External speaker
OPC-441	Speaker extension cable, 5.0m (16.4ft)

Mounting Bracket/ Base

MB58	Remote Control Head Bracket for IC-R1500
MB65	Mounting Base
MB84	Remote Control Head Bracket for IC-R2500